

## **DocuSign for Alfresco (BETA) Install Overview**

This document is designed to give instructions on installing the DocuSign for Alfresco (BETA) Connector in your Alfresco v3.4.x deployment. This Beta has been tested on 3.4.5 and 3.4.6, and should install on any 3.4.x environment.

## **Installation Process**

1. Stop Alfresco.

The commands to stop Alfresco are as follows, depending on where it is deployed.

If you are on LINUX, run /alfresco.sh stop from the \opt\alfresco-3.4.6\ directory (assuming you are on 3.4.6).

If you are using Windows, run the Alfresco Service – stop command from the Start menu

- 2. Download the ZIP file from the DocuSign Marketplace containing the AMPS file, and unzip the file.
- 3. Copy docusign-for-alfresco-core.amp to \alfresco\amps
- 4. Copy docusign-share-msss-action.amp to \alfresco\amps\_share

The following steps are highly recommended (The apply\_amps.bat normally does these steps automatically, but to double check the installation, perform the following steps as well)

- 5. Delete \alfresco\tomcat\webapps\work\\*.\*
- 6. Delete \alfresco\tomcat\webapps\alfresco\\*.\* [shift-delete on alfresco in windows dir and all directories]
- 7. Delete \alfresco\tomcat\webapps\share\\*.\* [shift-delete on share in windows to get dir and all directories]
- 8. Delete \alfresco\tomcat\logs\\*.\* [just delete the logs]
- 9. This step is important when installing DocuSign for Alfresco the first time.

Restore the original alfresco.war and share.war to the \alfresco\tomcat\webapps dir by copying them from a fresh install copy. Alternatively, you can delete the existing alfresco.war and share.war files and all but one of the bak files and rename that bak back to share.war / alfresco.war

- 10. Run \alfresco\bin\apply\_amps.bat
- 11. Start alfresco

If you are on LINUX, run /alfresco.sh start from the \opt\alfresco-3.4.6\ directory (assuming you are on 3.4.6).

If you are using Windows, run the Alfresco Service – start command from the Start menu